

Overview

Mutualink is an IP-based multimedia communication resource sharing platform that allows public safety agencies and critical community assets to communicate in a manner that is separate and apart from the general public.

Mutualink's IP-NIC Series of Secure Controllers embrace the integration of most IP-based communications systems. It is designed to provide connectivity to other IP devices that don't support analog interfaces. IP-NICs can be used to connect to VOIP Call Managers, IP video cameras, other 3rd party IP based radio systems, etc.

The IPT Gateway is built to support up to 10 ports for SIP Connections.



IP& IPT SPECIFICATIONS

IP-NIC M500-500 Series Multi-IPT Gateway U500-520-001



Rear View, IPT Gateway





For more information on any of our products or services please contact us:



mutualink.net



(866) 957-5465



info@mutualink.net



Meadquarters:

1269 South Broad Street Wallingford, CT 06492



Research & Development

3 Lan Drive Westford, MA 01886

313 S. Jupiter Road, Suite 110 Allen, TX 75002

Rochelaise #26 Bo. Guanajibo Mayagüez, PR 00682

MECHANICAL	DESCRIPTION
Case Construction:	Ultra Lightweight Aluminum
Case Finish/Color:	Chassis - Black
Case Dimensions (W x H x D):	19" x 1.75" x 11" 1RU Rack Mount 12" X 1.75" X 11" Desk Top
Weight:	3.3 lbs.
Front Display:	Keypad Display
Cooling System:	Processor Fan
Operating Environment:	0° C to 60° C / 32° F to 140° F
Shock Resistance:	1,500G, 0.5ms
Motherboard:	Intel Atom D525
Processor:	1.8 GHz Dual Core
Memory:	2GB RAM
SSD Drive:	120G Sata II 2.5"
Vibration:	2.17G (5-700Hz)

ELECTRICAL	DESCRIPTION
Power Requirements:	120 VAC current Draw=22w 12VDC current draw = 1.65 Amps
Power Supply:	120/240VAC Brick to 12VDC
Power Supply:	120/240VAC Brick to 12VDC
LAN Ports:	3 x LAN
Serial Data Ports:	1 x RS232
Video Ports:	1 x VGA
USB Ports:	2 x USB

MISCELLANEOUS	DESCRIPTION
Included Accessories:	AC Power Adapter & Cord 2 Rack Mounting Brackets 4 Rubber Feet for Desktop
Warranty:	1-Year Parts and Labor

December 2021